

Thermal Receipt Printers

HOP - E801

Features

- LAN / USB
- Auto Cutter



| Item | Parameters | |
|---------------------------------|----------------------------|--|
| Print parameters | Printing Method | Thermal Line |
| | Printing width | 72mm |
| | Resolution | 576 Dots/Line or 512 Dots/Line (8dots/mm, 203dpi) |
| | Print speed | 260mm/Second |
| | Interface | USB, Internet, Internet+USB+COM, Internet+USB+WIFI, USB+COM, USB+Bluetooth, USB+WIFI |
| | Line Spacing | 3.75mm (Can adjust line spacing by command) |
| | Line No. Character Size | FontA-48Lines/FontB-64Lines ANK character, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) |
| Bar code Character | Extended character set | PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai) |
| | Bar code | 1D bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8) CODE39/ITF/CODABAR/CODE93/CODE128 2D barcode: QRCODE |
| Graphics printing | Graphics printing | Supports bitmap download and print |
| Cutter | Cutter Function | Full cut/Half cut |
| Paper | Type | Thermal |
| | Width | 79.5±0.5mm |
| | Diameter | ≤80mm |
| | Feed method | Easy feed(Clameshell feed) |
| Print commands | Commands | ESC/POS |
| Power | Power Adaptor | Input: AC 100V-240V,50-60Hz Output: DC 24V/2.5A |
| | Cash Drawer | OutputDC 24V/1A |
| Buffer | Input Buffer | 2048K bytes |
| | NV Flash | 256K bytes |
| Physical characteristics | Weight | 1.15KG |
| | Dimension | 195*140*148(MM) |
| Environment | Working | Temp: 5 ~ 45°C, Humidity: 10 ~ 80% |
| | Storage | Temp: -10 ~ 50°C, Humidity: 10 ~ 90% (No dew) |
| Reliability parameter | Print Head Life | 150KM (print density≤12.5) |
| | Cutter Life | 1500,000times |
| Software | Driver | Android, IOS, Linux, Windows |