


Thermal Receipt Printers

Model No.

- HOP - H58 (USB)
- HOP - H58 (USB + Bluetooth)



Item	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing width	48mm
Bar code Character	Resolution	384 Dots/Line or 512 Dots/Line (8dots/mm, 203dpi)
	Print speed	90 mm/Second
	Interface	USB, USB+Bluetooth (1 to 1), USB+Bluetooth (1 to many)
	Line Spacing	3.75mm (Can adjust line spacing by command)
	Line No.	Font A-32Lines/FontB-42Lines
	Character	Simple, traditional Chinese-16 lines
	Character Size	Standard GB18030 simplified / traditional Chinese Fonts
		ANK character, Font A: 1.5×3.0mm (12×24 dots)
		Font B: 1.1×2.1mm (9×17 dots)
		Simplified/Traditional Chinese : 3.0×3.0mm (24×24 Dots)
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/ WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/ PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/ PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/ (PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8) CODE39/ITF/CODABAR/CODE93/CODE128 2D bar code: QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed method	Easy feed (Clamshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input: AC 100V-240V,50-60Hz Output: DC 12V/2.5A
	Cash Drawer Output	DC 12V/1A
Buffer	Input Buffer	4K bytes
	NV Flash	40K
Physical characteristics	Weight	590g
	Dimension	185*130*112(MM)
Environment	Working	Temp: 5 ~ 45°C, Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50°C, Humidity: 10 ~ 90% (No dew)
Reliability parameter	Print Head Life	100KM (print density≤12.5)
	Cutter Life	1000,000times
Software	Driver	Android, IOS, Linux, Windows